

STRATLOCK RAIL SYSTEM

BY FASTMOUNT

Setting the standard for panel mounting

PRODUCT SHEET

SL-RLE Stratlock® Rail - Large Extrusion

SPECIFICATIONS:

The Stratlock SL-RLE is a unique extrusion that can be used for both horizontal and vertical framing, removing the need for orientation-specific profiles. Install with the Stratlock Rail Connector Range to create a wall, corner, or ceiling connection with fixed or 180° adjustability. Fixes to existing substrate using appropriate fasteners. Ideal for the support of decorative panels in medium stress applications.

Available in 3 metre lengths, the SL-RLE can be cut and assembled in grid format using appropriate Stratlock connectors. One profile for both horizontal and vertical framing on walls and ceilings. Aluminium grade 6063 T5.

SL-RLE



USE WITH:
SL-RCF90



SL-RCA180



SL-RCAB180





MATERIAL:

Aluminium grade 6063 T5

MORE INFO:

Installation Guide SL-RCF90,
SL-RCA180, SL-RCAB180

INSTALLATION: Partially exploded through section showing typical installation method



Overall profile width 58mm
Overall profile depth 22.3mm

Creating and decorating aluminium framework has never been faster or more flexible. With only one profile required and adaptable connectors, the Stratlock Rail System is a foolproof way to create a consistent substrate for the perfect panel finish. For further information or technical support contact: info@fastmount.com

BENEFITS

- One extrusion for vertical and horizontal planes
- Reduction of installation time
- Lightweight aluminium
- Simple assembly - order & cut according to wall design
- Compatible with Stratlock Range clips for mounting large and heavyweight panels
- No special tools required for assembly
- CAD files available for easy specification

APPLICATIONS

- Walls and ceilings
- Commercial interior fit out
- Hotels, hospitals, retail, residential
- Fire-rated interiors
- Exhibitions
- Offices

www.fastmount.com